

# Atlas Copco

## PSA Oxygen Generators

OGP Series (capacity 0.6 - 56 l/s; flow 2 - 200 Nm<sup>3</sup>/h; purity 90% - 95%)



Atlas Copco's new oxygen generator uses Pressure Swing Adsorption technology to isolate oxygen molecules from other molecules in compressed air. The result is high purity oxygen at the outlet of the generator. The OGP series is a very cost-efficient source of oxygen used in various industries like waste water treatment, ozone production, health care, glass industry, and many others.

## Features and Benefits

### Ready to Use

- Only requires a supply of dry compressed air
- Plug-and-play
- No specialist installation or commissioning
- Fully automated and monitored including oxygen sensor as standard
- Performance guaranteed independent from temperature

### Cost Savings

- Low installation and running cost – highly efficient technology
- No additional costs such as order processing, refills and delivery charges
- Virtually service free

### Exceptional Convenience

- Continuous availability (24 hours a day, 7 days a week)
- Risk of production breakdown due to gas running out is eliminated

### Desired Purity

- Oxygen supply according to your need: from 90% to 95% purity
- Very easy to set up the device for other purity levels

### High Flow Capacity

- The wide product range and nitrogen flows up to 200 Nm<sup>3</sup>/h make the new OGP series ideal for applications such as waste water treatment, ozone production, health care, glass and many more

# Technical Specifications

90.00%	Oxygen capacity*			Air consumption		
	l/s	cfm	Nm <sup>3</sup> /h	l/s	cfm	Nm <sup>3</sup> /h
OGP 2	0.6	1.3	2.0	6.7	14.1	22.20
OGP 3	0.9	1.9	3.0	9.0	19.1	30.00
OGP 4	1.1	2.4	3.7	10.8	22.9	36.00
OGP 5	1.4	2.9	4.5	16.2	34.4	54.00
OGP 6	2.0	4.1	6.5	21.6	45.8	72.00
OGP 8	2.3	5.0	7.8	30.6	64.9	102.00
OGP 10	2.9	6.0	9.5	30.6	64.9	102.00
OGP 14	4.2	8.9	14.0	46.5	98.5	154.80
OGP 18	5.5	11.6	18.2	56.8	120.2	189.00
OGP 20	6.0	12.7	20.0	64.9	137.4	216.00
OGP 23	6.9	14.6	23.0	75.7	160.3	252.00
OGP 29	8.6	18.3	28.8	97.3	206.1	324.00
OGP 35	10.4	21.9	34.5	108.1	229.0	360.00
OGP 45	13.4	28.3	44.5	153.1	324.5	510.00
OGP 55	16.5	35.0	55.0	187.4	397.0	624.00
OGP 65	19.5	41.4	65.0	236.0	500.1	786.00
OGP 84	25.2	53.4	84.0	290.1	614.6	966.00
OGP 105	31.5	66.8	105.0	367.5	778.7	1224.00
OGP 160	46.5	98.6	155.0	551.3	1168.1	1836.00
OGP 200	60.1	127.2	200.0	663.0	1404.8	2208.00

\* Performance +/- 5%.

### Reference conditions:

Ambient temperature 20°C  
 Ambient pressure 1013 mbar  
 Unit inlet temperature 20°C  
 Inlet pressure 7.5 bar(g)  
 Unit outlet nitrogen purity 90%  
 Compressed air inlet quality ISO8573-1 class 1-4-1

### Outputs

Maximum compressed air inlet temperature 45°C  
 Maximum ambient temperature 45°C  
 Minimum compressed air inlet temperature 5°C  
 Minimum ambient temperature 0°C  
 Minimum compressed air inlet pressure 4 bar(g)  
 Maximum compressed air inlet pressure 10 bar(g)  
 Minimum oxygen purity 90%  
 Maximum oxygen purity 95%

