COMPRESSOR DATA SHEET

Rotary Compressor: Variable Frequency Drive

		pressor: Variable DATA - FOR COM			
1	Manufacturer: Atlas	s Copco			
	Model Number: ZR 250 VSD-125		Date:	12-17-2018	
2	Air-cooled x Water-cooled		Type:	Screw	
	Oil-injected x	Oil-free	# of Stages:	2	
3	Rated Operating Pressure		100	psig ^b	
4	Drive Motor Nominal Rating		335	hp	
5	Drive Motor Nominal Efficiency		95.3	percent	
6	Fan Motor Nominal Rating	(if applicable)	-	hp	
7	Fan Motor Nominal Efficier	n Motor Nominal Efficiency -		percent	
	Input Power (kW)		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d	
	277.7 Ma		1514	18.3	
OΨ	227.0		1264	18.0	
8*	181.2		1014	17.9	
	139.3		764	18.2	
	100.6 M		514	19.6	
O.I.		o d			
9*	Total Package Input Power	at Zero Flow ^{c, u}	20.8	kW	
	35.0				
	30.0				
10	H (W				
	Specific Power (KW/100 A CFM) 20.0			_	
	Specifi kW/100				
	15.0				
	0 100 200 30		900 1000 1100 1200 1300 14	00 1500 1600 1700	
		Capacity (AC : Graph is only a visual represer Axis Scale, 10 to 35, + 5kW/100ac X-Axis Scale, 0 to 25% ove	ntation of the data in Section 8 ofm increments if necessary above 3	15	

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES:

a. Measured at the discharge terminal point of the compressor package in accordance with

Member

- ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.

 b. The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ /min	<u>ft3 / min</u>	%	%	
Below 0.5	Below 15	+/- 7	+/- 8]
0.5 to 1.5	15 to 50	+/- 6	+/- 7	+/- 10%
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	

ROT 031

10/11 R7 This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.