	1 2 3 4 5	Oil-ir	MOI urer:	Compressor: Variable DEL DATA - FOR COM Atlas Copco			-
	2 3 4	Model Nur X Air-c Oil-in		_			
	3 4	x Air-c	mber:				
	3 4	Oil-ir		ZT90-150VSD STD	Date:	03-13-2019	
	4		ooled	Water-cooled	Type:	Screw	
	4		Oil-injected X Oil-free			2	1
-		Rated Operating Pressure			# of Stages: 151	psig ^b	
-	5	Drive Motor Nominal Rating			121	hp	
	3	Drive Motor Nominal Efficiency			95.0	percent	1
	6	Fan Motor Nominal Rating (if applicable)			4.0	hp	
[7	Fan Motor Nominal Efficiency			87.6	percent	1
	=	Input Power (kW)			Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d	
		104.6 Max			460	22.7	
	0.*	102.0			447	22.8	
	8*	99.4			433	23.0	
		96.8			420	23.0	
		94.3 Min			406	406 23.2	
	9*	Total Package Input Power at Zero Flow ^{c, d}			27.4	kW	_
	10	Specific Power (kW/100 A.CFM)		50 100 150 200 Capacity (A Note: Graph is only a visual repress Note: Y-Axis Scale, 10 to 35, + 5kW/100a X-Axis Scale, 0 to 25% ov	CFM) ntation of the data in Section 8 cfm increments if necessary above rr maximum capacity		
Memb CCA	Consult CA NOTES:	AGI website fo a. Measur ISO 12 b. The op c. No Loa manufa d. Tolerar NOTE:	r a list of part red at the discl 217, Annex E; berating pressu ad Power. In a acturer may sta nce is specified : The terms "p	I Performance Verification Progr ticipants in the third party verific harge terminal point of the compress acfm is actual cubic feet per minute re at which the Capacity and Electric cordance with ISO 1217, Annex E te "not significant" or "0" on the ter d in ISO 1217, Annex E, as shown in ower" and "energy" are synonymous olume Flow Rate pecified conditions <u>ft3/min</u> Below 15 15 to 50 50 to 500 Above 500	ation program: or package in accordance wit at inlet conditions. cal Consumption were measu if measurement of no load p t report. a table below:	www.cagi.org h red for this data sheet. ower equals less than 1%,	No Load / Zero Flow Power +/- 10%