

COMPRESSOR DATA SHEET

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Fixed Speed

	MODEL DATA - FOF	R COMPRESSED AIR	R (Preliminary Da	ata)
1	Manufacturer: A	tlas Copco		
	Model Number: G	A37+-100 WC	Date:	2/22/2024
2	0 Air-cooled	K Water-cooled	Type:	Screw
			# of Stages:	1
3*	Rated Capacity at Full Load Op	perating Pressure ^{a, e}	252	acfm ^{a,e}
4	Full Load Operating Pressure b		100	psig
5	Maximum Full Flow Operating	Pressure ^c	107	psig ^c
6	Drive Motor Nominal Rating		50	hp
7	Drive Motor Nominal Efficience	94.1		percent
8	Fan Motor Nominal Rating (if a	applicable)	NA	hp
9	Fan Motor Nominal Efficiency		N/A	percent
10*	Total Package Input Power at Z	Zero Flow ^e	10.7	kW ^e
11	Total Package Input Power at R Load Operating Pressure ^d	Rated Capacity and Full	42.9	kW^d
12*	Specific Package Input Power a Full Load Operating Pressure ^e	at Rated Capacity and	17.0	kW/100 cfm ^e
13	Isentropic Efficiency		78.07	Percent

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI websitefor a list of participants in the third party verification program: www.cagi.org

NOTES:

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.

Member



- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:
 - NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions			Consumption	Flow Power
$\underline{m^3 / \min}$	<u>ft3 / min</u>	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	
]	<u>m³ / min</u> Below 0.5 0.5 to 1.5 1.5 to 15	m^3 / min $ft3 / min$ Below 0.5 Below 17.6 0.5 to 1.5 17.6 to 53 1.5 to 15 53 to 529.7	m^3 / min $ft3 / min$ % Below 0.5 Below 17.6 +/- 7 0.5 to 1.5 17.6 to 53 +/- 6 1.5 to 15 53 to 529.7 +/- 5	$\underline{m^3 / \min}$ $\underline{ft3 / \min}$ % % Below 0.5 Below 17.6 +/- 7 +/- 8 0.5 to 1.5 17.6 to 53 +/- 6 +/- 7 1.5 to 15 53 to 529.7 +/- 5 +/- 6