

COMPRESSOR DATA SHEET

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Fixed Speed

| MODEL DATA - FOR COMPRESSED AIR (Preliminary Data) | | | | | | | |
|--|---|---------------------------|-------------------------|--------------------------|--|--|--|
| 1 | Manufacturer: | Atlas Copco | | | | | |
| | Model Number: | GA55+-150 WC | Date: | 2/21/2024 | | | |
| 2 | Air-cooled | X Water-cooled | Type: | Screw | | | |
| | | | # of Stages: | 1 | | | |
| 3* | Rated Capacity at Full Load Operating Pressure a, e | | 345.6 | acfm ^{a,e} | | | |
| 4 | Full Load Operating Pressure b | | 150 | psig b | | | |
| 5 | Maximum Full Flow Operating Pressure ^c | | 157 | psig | | | |
| 6 | Drive Motor Nominal Rating | | 75 | hp | | | |
| 7 | Drive Motor Nominal Efficiency | | 94.5 | percent | | | |
| 8 | Fan Motor Nominal Rating (if applicable) | | N/A | hp | | | |
| 9 | Fan Motor Nominal Efficiency | | NA | percent | | | |
| 10* | Total Package Input Power a | t Zero Flow ^e | 10.5 | kW ^e | | | |
| 11 | Total Package Input Power a Load Operating Pressure ^d | t Rated Capacity and Full | 68 | kW^d | | | |
| 12* | Specific Package Input Power at Rated Capacity and Full Load Operating Pressure 19.7 | | kW/100 cfm ^e | | | | |
| 13 | Isentropic Efficiency | | 84.07 | Percent | | | |

^{*}For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator.

Consult CAGI websitefor a list of participants in the third party verification program:

www.cagi.org

NOTES:

Member

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
 - d. Total package input power at other than reported operating points will vary with control strategy.
 - e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



| | ne Flow Rate fied conditions | Volume Flow Rate | Specific Energy Consumption | No Load / Zero Flow Power |
|------------|---------------------------------|------------------|-----------------------------|------------------------------|
| m³/min | <u>ft3 / min</u> | % | % | |
| Below 0.5 | Below 17.6 | +/- 7 | +/- 8 | |
| 0.5 to 1.5 | 17.6 to 53 | +/- 6 | +/- 7 | +/- 10% |
| 1.5 to 15 | 53 to 529.7 | +/- 5 | +/- 6 | |
| Above 15 | Above 529.7 | +/- 4 | +/- 5 | |

ROT 030.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.