

COMPRESSOR DATA SHEET

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Fixed Speed

	MODEL DATA - FOR	COMPRESSED AI	R (Preliminary D	ata)
1	Manufacturer: At	as Copco		
	Model Number: GA75+-150 WC		Date:	2/21/2024
2	0 Air-cooled X	Water-cooled	Type:	Screw
			# of Stages:	1
3*	Rated Capacity at Full Load Op	erating Pressure ^{a, e}	449.2	acfm ^{a,e}
4	Full Load Operating Pressure ^b	b 150		psig ^b
5	Maximum Full Flow Operating	erating Pressure ^c 157		psig ^c
6	Drive Motor Nominal Rating	g 100		hp
7	Drive Motor Nominal Efficiency	efficiency 95.0		percent
8	Fan Motor Nominal Rating (if a	pplicable)	N/A	hp
9	Fan Motor Nominal Efficiency		NA	percent
10*	Total Package Input Power at Ze	ero Flow ^e	14.7	kW ^e
11	Total Package Input Power at Ra Load Operating Pressure ^d	ated Capacity and Full	87.3	kW^d
12*	Specific Package Input Power as Full Load Operating Pressure ^e	Rated Capacity and	19.4	kW/100 cfm ^e
13	Isentropic Efficiency		85.11	Percent

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI websitefor a list of participants in the third party verification program: www.cagi.org

NOTES:

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.





- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
 c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:
 - NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions			Consumption	Flow Power
$\underline{m^3 / \min}$	<u>ft3 / min</u>	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	
]	<u>m³ / min</u> Below 0.5 0.5 to 1.5 1.5 to 15	m^3 / min $ft3 / min$ Below 0.5 Below 17.6 0.5 to 1.5 17.6 to 53 1.5 to 15 53 to 529.7	m^3 / min $ft3 / min$ % Below 0.5 Below 17.6 +/- 7 0.5 to 1.5 17.6 to 53 +/- 6 1.5 to 15 53 to 529.7 +/- 5	$\underline{m^3 / \min}$ $\underline{ft3 / \min}$ % % Below 0.5 Below 17.6 +/- 7 +/- 8 0.5 to 1.5 17.6 to 53 +/- 6 +/- 7 1.5 to 15 53 to 529.7 +/- 5 +/- 6