	Federal Unifor		SSOR DAT	TA SHEET Air Compressors Not	Applicable
		Rotary Cor	mpressor: I	Fixed Speed	
	I	MODEL DATA -	- FOR CON	APRESSED AIR	
1	Manufacturer:	Atlas Copco			
	Model Number	GA 250	W-8.6	Dat	e: 08-10-2020
2	Air-cooled	✓ Water-co	ooled	Тур	e: Screw
	✓ Oil-injected	Oil-free		# of Stage	s: 1
3*	Rated Capacity at Full Load Operating Pressure*(a,e)		1,468.9	(acfm) *(a,e)	
4	Full Load Operating Pressure*(b)		125.0	psig*(b)	
5	Maximum Full Flow Operating Pressure*(c)		132.0	psig*(c)	
6	Drive Motor Nominal Rating		300.0	hp	
7	Drive Motor Nominal Efficiency		96.2	percent	
8	Fan Motor Nominal Rating (if applicable)		0.5	hp	
9	Fan Motor Nominal Efficiency		30.0	percent	
10*	Total Package Input Power at Zero Flow*(e)		ow*(e)	55.7	kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			260.1	kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			17.7	kW/100 cfm*(e)
:	*For models that are tested in	the CAGI Performance V	/erification Prog	ram, these items are verified by	program administrator
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.org a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.				
Member	<ul> <li>b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.</li> </ul>				
	c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.				
AUI essed Air & Gas Institute	<ul> <li>d. Total package input</li> <li>e Tolerance is specified</li> </ul>	power at other than repor ed in ISO 1217, Annex E,	rted operating po as shown in tab	ints will vary with control strat le below:	egy.
	NOTE: The terms "power" and "energy" are synonymous for Volume Flow Rate		synonymous for	purposes of this document. Specific End	ergy No Load / Zero
	at specified conditions		Volume F	-	0,5
	<u>m3 / min</u>	<u>ft3 / min</u>	%	%	
	Below 0.5	Below 15		7 +/- 8	
	0.5 to 1.5 15 to 50		+/-	6 +/- 7	+/- 10
	1.5 to 15	1.5 to 15 50 to 500		5 +/- 6	
030.2	Above 15 Above 500 +/-		4 +/- 5		